

LED Sensor Panel

SPECIFICATIONS

VOLTAGE	220-240AC
POWER FACTOR	>0.90
CRI	>80
IP RATING	IP20
BEAM ANGLE	110°
INSTALL ACCESSORIES	Surface Mount Kit Recessed Frame Suspension Kit

Occupancy and Daylight built in Sensor:

MOUNTING HEIGHT	3.5m
DETECTION RANGE	8m Diameter
DAYLIGHT THRESHOLD	450 Lux
MOTION HOLD	20mins
STANDBY	30% dim
ACCESSORIES	Remote Control



ILUMINOUS MODELS

MODEL	POWER	LCP	LUMEN	DIMENSIONS	CCT
PPAN18W3X124KCS PPAN18W3X125KCS PPAN18W3X126KCS	18w	17.4w	2340	295*1195*30mm	4000K 5000K 6000K
PPAN20W3X124KCS PPAN20W3X125KCS	20w	19.7w	2600	295*1195*30mm	4000K 5000K
PPAN25W3X124KCS PPAN25W3X125KCS	25w	24w	3250	295*1195*30mm	4000K 5000K
PPAN20W6X64KCS PPAN20W6X65KCS	20w	19.3w	2600	595*595*30mm	4000K 5000K
PPAN25W3X124KC* PPAN25W3X125KC*	25w	24w	3250	295*1195*30mm	4000K 5000K

*without sensor

GET IN TOUCH

 info@primsal.com

 primsal.com